



Product Service

# EU-Type Examination Certificate

No. P5A 089530 0019 Rev. 00

**Holder of Certificate:** **TruBlue LLC**  
**dba Head Rush Technologies**  
1699 Cherry Street  
Louisville CO 80027  
USA

**Product:** **PPE against fall from a height**  
**Pulley EN 12278**

**Model(s):** **Redirection Pulley**

**Tested according to:** DIN EN 12278:2007

The Certification Body of TÜV SÜD Product Service GmbH confirms that the listed product fulfils the basic requirements with Annex V (Module B) of Regulation (EU) 2016/425 on personal protective equipment according to Article 19 (PPE of category III). This certificate refers only to the submitted sample for testing and certification and on its technical documentation. The validity of this certificate based on an ongoing surveillance in accordance with Module C2 or D of Regulation (EU) 2016/425 by a Notified Body. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713356274

**Valid from:** 2025-02-13

**Valid until:** 2030-02-12

**Date,** 2025-02-13

( Matthias Völz )

# EU-Type Examination Certificate

No. P5A 089530 0019 Rev. 00

## Parameters:

Old EU-type examination certificate:	P5A 089530 0009 Rev. 00
Old technical report:	713166756
Type:	Pulley EN 12278, type Redirection Pulley
Construction:	Open body form
Dimensions:	86 mm x 52 mm x 25 mm; body sheets up to 5.5 mm thick
Attachment point:	Ø 16 mm;
Rope placement:	Body sheets turn around pulley axis;
Pulley wheel:	Ø 44.6 mm x Ø 12.6 mm; rope radius 3.65 mm; 1 ball bearings Ø 28 mm x 7 mm; rivet Ø 8 mm;
Max rope diameter	7 mm
Weight:	129 g
Guaranteed break strength:	18 kN
Marking:	model, manufacturer address, max rope diameter; guaranteed strength with pictogram; EN 12278; CE-marking; manufacturing date;

